

Temperature & Model Dip-Switch Settings for B16 (50 PRESET) - REU VR1620WB50AK ONLY



- Confirm that ALL DIGITS of the model number on the appliance dataplate match the model numbers above.



- Dipswitch settings must only be set by an authorised person.
- All dipswitches MUST be set for the particular model in accordance with this Instruction. Incorrect dipswitch settings may result in a dangerous condition or damage to the appliance.

Dipswitch Settings

Dip Switches Explained & Model Setting

Off On SW 1

Model Type Factory Set

Temperatures

Gas Pressures

Off On SW 2

Gas Type

Model Type

Gas Type

Off On SW 2

Natural Gas

Propane Gas

Gas Pressures

Off On SW 1

Normal Combustion

Off On SW 1

Forced low Combustion

Off On SW 1

Note: After setting gas pressures return both 7 and 8 dipswitches to the OFF position for normal combustion.

Forced High Combustion

Model Type

Off On SW 1

REU-VR1620WB (50)
(B16 - 50° preset)

Off On SW 2

Temperature

Temperature dipswitch settings cannot be adjusted on factory preset 50°C models, Contact TSD for further information.

The temperature setting of the unit can be changed in small increments to achieve no more than 50°C at all hot water fixtures. See separate instruction for this.

Legend

Black indicates position of switch

SW 1

SW 2
