## Temperature & Model Dip-Switch Settings for B24 (60°C) - REU VR2426WB60AK ONLY



Confirm that <u>ALL DIGITS</u> of the model number on the appliance dataplate match the model numbers above.



- Dipswitch settings must only be set by an authorised person.
- All dipswitches MUST be set for the particular model in accordance with this Instruction. Incorrect dipswitch settings may result in a dangerous condition or damage to the appliance.

## **Dipswitch Settings** Temperature Dip Switches Explained & Model Setting Gas Type 1 2 3 4 5 6 7 8 1 2 3 4 5 6 7 Off On SW 2 Natural Gas 1 2 3 4 40°C 42°C 3 4 5 6 7 8 Temperatures Off On SW 2 Gas Pressures Propane Gas 1 2 1234567 1 2 3 3 4 5 6 7 8 50°C 55°C Model Type **Model Type** SW 1 SW 1 Off On SW 1 1 2 3 4 5 6 7 1 2 3 4 5 6 7 2 3 4 5 6 7 60°C 65°C REU-VR2426W**B**(60) (B24 - 60° Preset) Normal Combustion 1 2 SW 1 3 4 5 2 3 4 5 6 7 75°C 6 7 Forced low Combustion SW 1 Note: After setting gas pressures return both 7 and 8 dipswitches to the OFF position for normal combustion. 6 7 Forced High Combustion Legend If the dipswitch bank 2 has 6 switches. Ensure that switches 5 and Black indicates position of switch 6 are in the OFF position