

		Specification of Rinnai Air Conditioner R410A Split Type Wall Mounted			
Model No.			RINV25R-A	RINV35R-A	RINV70R-A
			RINV25RHDR-A (Indoor unit) RINV25RCMP-A (Outdoor unit)	RINV35RHDR-A (Indoor unit) RINV35RCMP-A (Outdoor unit)	RINV70RHDR-A (Indoor unit) RINV70RCMP-A (Outdoor unit)
Type	Air Conditioner (AC)				
Cooling Capacity		W	2500(1500~3200)	3450(1400~4100)	7000(2500-8000)
Heating Capacity		W	2700(1400~4100)	3550(1700~4600)	6400(2500-8500)
EER /COP		W/W	3.83/3.97	3.66/3.86	3.29/3.37
Energy Star For Cooling			3	2.5	2
Energy Star For Heating			3.5	2.5	2
Moisture Removal		Litres/h	0.7	0.9	2
Indoor Noise Level		dB (A)	39	42	52
Outdoor Noise Level		dB (A)	51	53	60
Electrical Data					
Power Supply	220-240V~/50HZ				
Rated Current	Cooling	A	3.9 (1.75~7.8)	4.82(1.8~8.1)	9(3.4-14)
	Heating	A	4.1(2.2~8.1)	4.8(1.8~8.3)	8.5(3.5-14.2)
Rated Input	Cooling	W	680(350~1330)	930(350~1650)	2050(750-3150)
	Heating	W	690(370~1420)	960(320~1750)	1900(3200-7000)
Max Current Input		A	8.1	8.3	15
Max Power Input		W	1420	1750	3400
Refrigerating System					
Refrigerat	R410A	G	1130	1230	2450
Compressor	Type		Variable Output	Variable Output	Variable Output
Fan System					
Indoor Air Circulation/Hi Cooling		m³/h	620	650	1,200
Indoor Fan Type			Cross Flow	Cross Flow	Cross Flow
Outdoor Fan Type			Propeller Fan	Propeller Fan	Propeller Fan
Outdoor Fan Speed		rpm	700±30	770±30	900±30
Connections					
Connecting Pipe	Liquid	Inches	1/4"	1/4"	3/8"
	Gas	Inches	3/8"	1/2"	5/8"
Others					
Net Dimensions (W*D*H)	Indoor	mm	880*286*205	880*286*205	1185*322*235
	Outdoor	mm	760*540*260	760*540*260	902*795*332
Net Weight	Indoor	kg	10.5	10.5	18
	Outdoor	kg	32	32	61
Packing Dimensions	Indoor	mm	935*336*255	935*336*255	1300*440*380
	Outdoor	mm	880*370*600	880*370*600	1030*430*860